

Heidelberg Materials

Tanzania Portland Cement Public Limited Company P.O.Box 1950,Dar es Salaam-Tanzania Telephone: +255 746 810930

Fax: +255 746 810931 www.twigacement.com

MONTHLY CERTIFICATE OF CHEMICAL & PHYSICAL TESTS TWIGA PLUS, CEM II/B-M CLASS 42.5 N MAY, 2024

Sampled and tested in accordance with the requirements of the Tanzanian Bureau of Standards

TZS 727-1/EAS 18-1

	CHEMICAL TI	EST RESULTS	
Test	Unit	Test results	Specified requirements
Loss on Ignition	[%]	8.16	No requirement
Insoluble Residues	[%]	1.20	Less than 5.0%
CaO	[%]	56.4	No requirement
SiO ₂	[%]	19.7	No requirement
CaO/SiO ₂	[-]	2.87	Not less than 2.0%
Al ₂ O ₃	[%]	4.72	No requirement
Fe ₂ C ₃ .	[%]	2.88	No requirement
Ogle	[%]	1.51	Not more than 5.0%
SO ₃	[%]	2.46	Less than 3.5%
K ₂ O	[%]	0.42	No requirement
Na ₂ O	[%]	0.25	No requirement
P ₂ O ₅	[%]	0.18	No requirement
TiO ₂	[%]	0.75	No requirement
MnQ	[%]	0.08	No requirement
(Na ₂ O+ 0.658 K ₂ O)	[%]	0.52	No requirement
Cl	[%]	0.001	Less than 0.10%
	PHYSICAL TE	ST RESULTS	
Density	[kg/m3]	3100	No requirement
Specific Surface (Blaine)	[m²/kg]	452	No requirement
Sieving Residue on 45 mic. mesh	[%]	9.2	No requirement
Initial Setting Time	[Minutes]	145	Not less than 60 minutes
Soundness (Expansion)	[mm]	1.0	Not more than 10.0 mm
Compressive Strength 2 days	[MPa]	18.2	More than 10.0 MPa
Compressive Strength 28* *days*	[MPa]	44.1	Between 42.5 and 62.5 Mpa

Remarks: * The 28 days strength is the average of previous month.

Wazo Hill, 2024/06/05th

Quality Control Manager

Plant Manager

Ruth Zaipuna (Tanzanian) Gary Whitehead (British) Oswald Urassa (Tanzanian) Commercial Director

Board Directors: Hakan Gurdal (Turkish) Alfonso Velez (Spanish) Francesco Brambilla (Italian)