

Heidelberg Materials

Tanzania Portland Cement Public Limited Company

P.O.Box 1950, Dar es Salaam-Tanzania

Telephone: +255 746 810930 Fax: +255 746 810931 www.twigacement.com

MONTHLY CERTIFICATE OF CHEMICAL AND PHYSICAL TESTS

TWIGA EXTRA, CEM II/B-L CLASS 32.5 R

OCTOBER, 2024

Sampled and tested in accordance with the requirements of the Tanzanian Bureau of Standards

TZS 727-1/EAS 18-1. Equivalent to EN 197-1

	CARRITATION	L TEST RESULTS):
Test	Unit	Test results monthly average	Specified requirements
Loss on ignition	[%]	12.0	No Requirement
Insoluble Residue	[%]	1.24	Less than 5.0%
CaO	[%]	56.3	No Requirement
SiO ₂	[%]	18.4	No Requirement
CaO/SiO ₂	[-]	3.06	Not less than 2.0%
Al ₂ O ₃	[%]	4.80	No Requirement
Fe ₂ O ₃	[%]	3.02	No Requirement
MgO	[%]	1.03	Not more than 5.0%
SO ₃	[%]	2.55	Less than 3.5%
K₂O	[%]	0.40	No Requirement
Na ₂ O	[%]	0.17	No Requirement
P ₂ O ₅	[%]	0.49	No Requirement
ΓiO ₂	[%]	0.52	No Requirement
MnO	[%]	0.06	No Requirement
Na ₂ O+0.658K ₂ O)	[%]	0.44	No Requirement
Cl	[%]	0.002	Less than 0.10%
Market and the second	PHYSICAL	TEST RESULTS	
Density	[kg/m³]	3100	No requirement
Specific Surface (Blaine)	[m²/kg]	452	No Requirement
Sieving Residue on 45 mic.	[%]	11.9	No Requirement
nitial setting time	[minutes]	168	Not less than 75 minutes
Soundness (expansion)	[mm.]	1.0	Not more than 10 mm.
Compressive strength 2 days	[MPa]	14.0	More than 10 MPa.
Compressive strength 28 days*	[MPa]	35.4	Between 32.5 and 52.5 MPa

Remarks: *The 28 days strength is the average of previous month.

Quality Control Manager

Plant Manager

Commercial Director

Board Directors: Hakan Gurdal (Turkish) Alfonso Velez (Spanish) Francesco Brambilla (Italian)

Ruth Zaipuna (Tanzanian) Gary Whitehead (British) Oswald Urassa (Tanzanian)