

## **Heidelberg Materials**

**Tanzania Portland Cement Public Limited Company** P.O.Box 1950, Dar es Salaam-Tanzania

Telephone: +255-746 810 930 Fax: +255-746 810 931 Info@twigacement.com www.twigacement.com

## MONTHLY CERTIFICATE OF CHEMICAL AND PHYSICAL TESTS TWIGA ORDINARY, CEM I CLASS 42.5 N

## NOVEMBER, 2024

Sampled and tested in accordance with the requirements of the Tanzanian Bureau of Standards

TZS 727-1/EAS 18-1. Equivalent to EN 197-1

	CHEMIC	AL TEST RESULTS	
Test	Unit	Test results monthly average	Specified requirements
Loss on ignition	[%]	4.63	Less than 5.0%
Insoluble residue	[%]	1.00	Less than 5.0%
CaO	[%]	60.5	No Requirement
SiO <sub>2</sub>	[%]	20.5	No Requirement
CaO/SiO <sub>2</sub>	[-]	2.95	Not less than 2.0%
Al <sub>2</sub> O <sub>3</sub>	[%]	5.03	No Requirement
Fe <sub>2</sub> O <sub>3</sub>	[%]	3.31	No Requirement
MgO	[%]	1.01	Not more than 5.0%
SO <sub>3</sub>	[%]	2.54	Less than 3.5%
K <sub>2</sub> O	[%]	0.41	No Requirement
Na <sub>2</sub> O	[%]	0.16	No Requirement
P <sub>2</sub> O <sub>5</sub>	[%]	0.31	No Requirement
TiO <sub>2</sub>	[%]	0.44	No Requirement
MnO	[%]	0.06	No Requirement
(Na <sub>2</sub> O+0.658K <sub>2</sub> O)	[%]	0.43	No Requirement
CI <sup>-</sup>	[%]	0.001	Less than 0.10%
	PHYSICA	L TEST RESULTS	
Density	[kg/m³]	3000	No requirement
Specific Surface (Blaine)	[m²/kg]	362	No Requirement
Sieving Residue on 45 mic.	[%]	12.5	No Requirement
Initial setting time	[minutes]	119	Not less than 60 minutes
Final setting time	[minutes]	187	No Requirement
Soundness (expansion)	[mm.]	1.0	Not more than 10 mm.
Compressive strength 2 days	[MPa]	21.2	More than 10 MPa.
Compressive strength 28 days*	[MPa]	50.0	Between 42.5 and 62.5 MPa

Remarks: \*The 28 days strength is the average of previous month.

Wazo Hill 2024/12/03rd

Quality Control Manager

Plant Manager

Commercial Director